

T4eS

簡單易懂好操作，您最佳的選擇

*Easy
your work*



特色：



- 3D立體化指示燈
- 狀態一目了然
- 超大記憶體，超大儲存空間
- 超高的性價比
- 搭配專業級標籤編輯軟體

SBARCO
THE ONE YOU CAN RELY ON



型號	T4ES
解析度	203 /300 dpi
列印模式	熱感式及熱轉式兩用
中央處理器	32-bit CPU
Memory	● RAM: 64MB SDRAM ● ROM: 128MB Flash ROM
列印速度	203 dpi 1 to 5 ips (選配 6 ips)/300 dpi 1 to 4 ips
最大列印長度	150 inches
最大列印寬度	4.1" (104mm)
感測器	● 可移動反射式感應器 ● 碳帶感應器 ● 印字頭開啟感應器
操作面板	1個多功能按鍵及LED指示燈(紅色，藍色，紫色)
紙張	● 紙張寬度: 0.59"(15mm)~4.33" (110mm) ● 紙捲最大直徑: 5" (127mm) ● 紙捲軸心直徑: 1.0" (25.4mm) ● 紙張厚度: 0.002" (0.06mm) to 0.0075" (0.2mm) ● 紙張類型:連續紙、間隙紙、折疊紙、黑線標紙、吊牌(外內捲紙皆可)
碳帶	● 外徑: 1.535" (39mm) ● 最大長度: 100m ● 寬度: 1.0" (25.4mm) to 4.3" (110mm) ● 軸心直徑: 0.5" (12.7mm) ● 材質: 一般蠟質型、混合型、抗刮樹脂型
傳輸介面	● 序列埠–RS–232(選配) ● USB slave port ● 選配: 乙太網路模組 10/100Mbps 、藍牙模組、Wifi模組
一維條碼	Code39 standard or extended, Code39 with check digit, Code93, Code128 UCC, Code128 auto A,B,C modes, Codabar, EAN8, EAN8/13 2&5 digit add-on, EAN13, Interleaved 2 of 5, Interleaved 2 of 5 with check digit, Interleaved 2 of 5 with human readable check digit, UCC/EAN 128, UPC A, UPC A 2&5 digit add-on, UPC E, UPC E 2&5 digit add-on, UPC Interleaved 2 of 5、Code 11
二維條碼	Data Matrix, MaxiCode, PDF417, QR code
字型	● 5種內建可擴充bitmap字型 (字母–數字) ● 2種內建可擴充bitmap字型(僅數字) ● 可下載的soft font ● 4種旋轉角度: 0, 90, 180, 270
圖形	PCX, Direct binary graphic, BMP, HEX
選配	● 剝紙模組 ● 藍牙模組 ● 裁刀 ● 乙太網路模組
電源	● 電壓自動切換電源供應器 ● 輸入: 100 to 240V, 1.8A, 50~60Hz ● 輸出: 24V, 2.5A
工作環境	● 操作溫度: 5°C to 45°C(40°F to 112.9°F) ● 儲存溫度: -20°C to 50°C (-4°F to 121.9°F)
濕度	● 操作濕度: 10% to 90% non condensing ● 儲存濕度: 5% to 95% non condensing
印表機尺寸	● 寬度: 200.00mm (7.83") ● 長度: 263.19mm (10.36") ● 高度: 188.29mm (7.41") ● 重量: 2KG
安規認證	CE, FCC class A, CB, CCC, BSMI

上述規格以實機為主，如有變更，不另行通知。

傳勝科技有限公司

www.dwin.com.tw